

CONNECT 245 VAC-TRUCK



Tapered flange coupling system to fit adapter acc. to DIN 3016-3

Applications

- suction excavator
- municipal vehicle: sweeper, sweeping machine

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- When used vertically user must secure flange and hose with additional attachments
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured
- gas and liquid tight as pre-fitted version

| Size (mm) | Outer-Ø flange (mm) | Total Length (mm) | Weight (kg/pcs) | Suitable for Hose I.D. (mm) | item | Order No. |
|-----------------------------------------------|---------------------------|-------------------------|--------------------|-----------------------------------|---------------------------------------------------------|---------------|
| standard version, 80 Shore D approx. | | | | | | |
| 250 | 295 | 108 | 1,00 | 356-0250-0000 | tapered flange, black, for screwing on | 245-0250-8501 |
| 250 | 295 | 108 | 1,00 | 355-0254-5202 | tapered flange, black, for screwing on | 245-0250-8507 |
| Soft version, 85 Shore A approx. | | | | | | |
| 250 | 295 | 108 | 1,00 | 356-0250-0000 | tapered flange, black, for screwing on | 245-0250-8505 |
| pre-fitted, 85 Shore D approx. | | | | | | |
| 250 | 295 | 119 | 1,61 | 356-0250-0000 | tapered flange, black, moulded | 245-0250-8573 |
| 250 | 295 | 108 | 1,00 | 355-0254-5202; 356-0250-0000 | reinforced tapered flange, black, moulded | 245-0250-8754 |
| Reinforced version, 85 Shore D approx. | | | | | | |
| 250 | 295 | 108 | 1,00 | 356-0250-0000 | Reinforced tapered flange, black, for screwing on | 245-0250-8701 |
| Clamps | | | | | | |
| 250 | - | - | 1,50 | - | Reinforced quick- release clamp | 245-0250-8755 |
| 250 | - | - | 1,240 | - | Quick-Release clamp | 245-0250-8911 |

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.