



## Tapered flange coupling system to fit adapter acc. to DIN 3016-3

### Applications

- suction excavator
- municipal vehicle: sweeper, sweeping machine

### Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline
- When used vertically user must secure flange and hose with additional attachments
- REACH according to --> Technology / Technical Information / REACH

### Temperature range

- -40°F to 195°F

### Design

- wall: special premium ether-polyurethane (Pre-PUR®)

### Delivery variants

- further diameters available on request
- black (standard)
- special colors: full colored
- gas- and liquid-tight as pre-fitted version

Size (in)	Outer-Ø flange (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	item	Order No.
<b>standard version, 80 Shore D approx.</b>						
9.843	11.614	4.252	2.205	356-0250-0000	tapered flange, black, for screwing on	245-0250-8501
9.843	11.614	4.252	2.205	355-0254-5202	tapered flange, black, for screwing on	245-0250-8507
<b>Soft version, 85 Shore A approx.</b>						
9.843	11.614	4.252	2.205	356-0250-0000	tapered flange, black, for screwing on	245-0250-8505
<b>pre-fitted, 85 Shore D approx.</b>						
9.843	11.614	4.685	3.550	356-0250-0000	tapered flange, black, moulded	245-0250-8573
9.843	11.614	4.252	2.205	355-0254-5202; 356-0250-0000	reinforced tapered flange, black, moulded	245-0250-8754
<b>Reinforced version, 85 Shore D approx.</b>						
9.843	11.614	4.252	2.205	356-0250-0000	Reinforced tapered flange, black, for screwing on	245-0250-8701
<b>Clamps</b>						
9.843	0.000	0.000	3.308	-	Reinforced quick- release clamp	245-0250-8755
9.843	0.000	0.000	2.734	-	Quick-Release clamp	245-0250-8911