



Spiral hose connector for connecting, lengthening or repairing spiral hoses

## Applications

- industrial vacuum cleaners, vacuum cleaners

## Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- Permanently antistatic wall: electrical and surface resistance approx.  $10^9 \Omega$
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Temperature range

- -40 °F to 195 °F
- short time to 255 °F

## Design

- wall: special premium ether-polyurethane (Pre-PUR®)

## Delivery variants

- further diameters available on request
- special colors: full colored

Size	Threading depth hose	Total Length	Weight	Suitable for hose I.D.	Order No.
(in)	(in)	(in)	(lb/pcs)	(in)	
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
0.984	1.260	2.795	0.265	25	246-0025-8500
1.260	1.260	2.795	0.331	32	246-0032-8500
1.496	1.457	3.268	0.375	38	246-0038-8500
1.575	1.457	3.268	0.353	40	246-0040-8500
1.969	1.654	3.740	0.551	50	246-0050-8500
2.362	1.850	4.134	0.662	60	246-0060-8500
2.756	1.850	4.134	0.728	70	246-0070-8500
3.150	2.047	4.606	0.882	80	246-0080-8500
3.937	2.244	5.000	1.433	100	246-0100-8500
Threaded; Suitable for Hose 356					
1.260	1.260	2.795	0.331	32	246-0032-8501
1.496	1.457	3.268	0.375	38	246-0038-8501
1.575	1.457	3.268	0.353	40	246-0040-8501
1.969	1.654	3.740	0.551	50	246-0050-8501
2.362	1.850	4.134	0.662	60	246-0060-8501
2.756	1.850	4.134	0.728	70	246-0070-8501
3.150	2.047	4.606	0.882	80	246-0080-8501
3.937	2.244	5.000	1.433	100	246-0100-8501