



Spiral hose connector for connecting, lengthening or repairing spiral hoses, foodgrade

## Applications

- food industry, pharmaceutical industry: food, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses
- industrial vacuum cleaners, vacuum cleaners

## Properties

- easily and quickly fitted

- re-usable (threaded version)
- highly abrasion resistant
- Food grade wall, complies with: EU-Directive 10/2011, EC 1935/2004 and EU 2015/174
- odorless and tasteless
- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

## Temperature range

- -40 °F to 195 °F
- short time to 255 °F

## Delivery variants

- special colors: full colored
- further diameters available on request

| Size<br>(in)  | Threading<br>depth hose<br>(in) | Total<br>Length<br>(in) | Weight<br>(lb/pcs) | Suitable for<br>hose I.D.<br>(in) | Order No.     |
|---|---------------------------------|-------------------------|--------------------|-----------------------------------|---------------|
| <b>Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345</b> |                                 |                         |                    |                                   |               |
| 0.984   | 1.260                           | 2.795                   | 0.265              | 25                                | 246-0025-8600 |
| 1.260   | 1.260                           | 2.795                   | 0.331              | 32                                | 246-0032-8600 |
| 1.496   | 1.457                           | 3.268                   | 0.375              | 38                                | 246-0038-8600 |
| 1.575   | 1.457                           | 3.268                   | 0.353              | 40                                | 246-0040-8600 |
| 1.969   | 1.654                           | 3.740                   | 0.551              | 50                                | 246-0050-8600 |
| 2.362   | 1.850                           | 4.134                   | 0.662              | 60                                | 246-0060-8600 |
| 2.756   | 1.850                           | 4.134                   | 0.728              | 70                                | 246-0070-8600 |
| 3.150   | 2.047                           | 4.606                   | 0.882              | 80                                | 246-0080-8600 |
| 3.937   | 2.244                           | 5.000                   | 1.433              | 100                               | 246-0100-8600 |
| <b>Threaded; Suitable for Hose 356</b>                          |                                 |                         |                    |                                   |               |
| 1.969   | 1.654                           | 3.740                   | 0.551              | 50                                | 246-0050-8601 |
| 2.362   | 1.850                           | 4.134                   | 0.662              | 60                                | 246-0060-8601 |
| 3.937   | 2.244                           | 5.000                   | 1.433              | 100                               | 246-0100-8601 |