

CONNECT STORZ DIN ALU 251



Storz suction coupling

Applications

- construction industry: lowering groundwater

- wood pellet heating system: conveying of wood pellets

Properties

- DIN design - forged aluminium (52-C = DIN 14321 / 75-B = DIN 14322 / 110-A = DIN 14323)
- Not to be used for explosive fluids group 1 and not according to pressure equipment directive
- REACH according to --> Technology / Technical Information / REACH

| Size (mm) | Lug Spacing (mm) | Weight (kg/pcs) | Suitable for Hose I.D. (mm) | Order No. |
|--|------------------------|--------------------|-----------------------------------|---------------|
| with corrugated nozzle for band clamp fitting; suitable to CONNECT 229 CLAMP ASSEMBLY | | | | |
| 52-C | 66 | 0,35 | 50 | 251-0050-8012 |
| 75-B | 89 | 0,66 | 75 | 251-0075-8012 |
| 110-A | 133 | 1,84 | 100 | 251-0100-8012 |
| with smooth nozzle and locking ring for clamp shell band fitting; suitable to CONNECT 231 SAFETY CLAMP ASSEMBLY | | | | |
| 52-C | 66 | 0,35 | 50 | 251-0050-8022 |
| 75-B | 89 | 0,66 | 75 | 251-0075-8022 |
| 110-A | 133 | 1,84 | 100 | 251-0100-8022 |
| replacement seal NBR back | | | | |
| 52-C | 66 | 0,02 | - | 251-0052-8068 |
| 75-B | 89 | 0,03 | - | 251-0075-8068 |
| 110-A | 133 | 0,05 | - | 251-0110-8068 |

Accessories



CLAMP 211

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.