

# CONNECT KAMLOK ALU 253



Kamlok coupling

## Applications

- silo, silo vehicle/ silo truck, tanker/ tank truck: silo charging, silo discharging
- for conveying of dry media and liquids

## Properties

- fluted nozzle for band clamp fitting
- Not to be used for explosive fluids group 1 and not according to pressure equipment directive

- REACH according to --> Technology / Technical Information / REACH

## Design

- material: aluminium

Size (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
<b>replacement seal NBR back</b>			
1.969	0.040	-	253-0050-8068
3.937	0.075	-	253-0100-8068
<b>female part, type C, suitable for CONNECT 229 CLAMP ASSEMBLY</b>			
1.969	0.970	51	253-0050-8212
3.150	2.051	76	253-0075-8212
3.937	2.844	102	253-0100-8212
<b>male part, type E, suitable for CONNECT 229 CLAMP ASSEMBLY</b>			
1.969	0.838	51	253-0050-8412
3.150	1.477	76	253-0075-8412
3.937	2.315	102	253-0100-8412
-			

## Accessories



CLAMP 211

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at [www.norres.com/us/technology/](http://www.norres.com/us/technology/). NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.