

CONNECT KARDAN 254



Kardan coupling

Applications

- construction industry: lowering groundwater
- for conveying of dry media and liquids

Properties

- Not to be used for explosive fluids group 1 and not according to pressure equipment directive
- REACH according to --> Technology / Technical Information / REACH

Design

- material: galvanized steel
- incl. sealing ring made of NBR

Size (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
female part			
1.969	2.761	51	254-0050-8211
3.504	8.820	76	254-0075-8211
4.252	12.017	102	254-0100-8211
5.236	15.832	127	254-0125-8211
6.260	36.537	152	254-0150-8211
male part			
1.969	1.096	51	254-0050-8411
3.504	2.448	76	254-0075-8411
4.252	3.162	102	254-0100-8411
5.236	5.513	127	254-0125-8411
6.260	7.938	152	254-0150-8411

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.