



## Layflat water hose

### Applications

- for various agricultural applications (dung transport and irrigation / sprinkling)
- for discharge and supply of industrial water (including hot water), pumps, sewer cleaning, cable protection and various other heavy industrial applications
- Suitable for air and dung
- for firefighting
- Cable protection

### Properties

- limited lye and acid resistance
- high tensile strength due to heavy duty reinforcements
- inner tube resistant to petrol and oil
- construction cover resistant to ageing, ozone, UV and weathering
- according to the norm EN ISO 1307:2008

### Temperature Range

- -20 °C to 80 °C

- short time to 100 °C
- Max. temperature hot water: 80 °C

### Design

- NBR/PVC inner layer
- NBR/PVC outer layer
- Außendecke gerieft

### Delivery variants

- black inner tube, black exterior wall

I.D.	outer Ø	Wall Thickness	Hose flat measured	Operating pressure (20 °C)	Max. operating pressure air	Burst pressure (20 °C)	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(mm)	(mm)	(bar)	(bar)	(bar)	(kg/m)	(m)	
0,75 / 20	24.00	2.00	30,00	25,000	18,000	75,000	0.18	<b>20 100</b>	3070-019-000
1 / 26	30.40	2.20	39,00	25,000	18,000	75,000	0.21	<b>20 100</b>	3070-025-000
1,25 / 32	36.40	2.20	50,00	20,000	15,000	60,000	0.24	<b>100</b>	3070-032-000
1,5 / 38	42.60	2.30	60,00	16,000	12,000	50,000	0.30	<b>20 100</b>	3070-038-000
2 / 52	57.00	2.50	82,00	16,000	12,000	50,000	0.40	<b>20 100</b>	3070-050-000
3 / 76	81.80	2.90	118,00	16,000	12,000	50,000	0.65	<b>20 100</b>	3070-075-000
3,5 / 90	96.60	3.30	141,00	16,000	12,000	50,000	0.90	<b>100</b>	3070-090-000
4 / 102	108.60	3.30	160,00	16,000	12,000	50,000	1.00	<b>20 100</b>	3070-100-000
5 / 127	134.00	3.50	196,00	14,000	10,000	42,000	1.40	<b>20 100</b>	3070-125-000
6 / 152	159.40	3.70	239,00	14,000	10,000	42,000	1.80	<b>20 50</b>	3070-150-000
8 / 203	210.80	3.90	319,00	10,000	7,000	30,000	2.60	<b>50</b>	3070-200-000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).