## PROTAPE® PUR-C 335 FOOD-AS FLAT





















Screening machine hose and compensator, vibration resistant

## **Applications**

- · food industry, pharmaceutical industry: food, pharmaceutical
- conveying of dry foods e.g. rice, cereals, sugar, milk powder, powders, coffee, tea, grains, flour,
- · mixer, dryer, packaging machine, bulk-bag (big bag)-charging and discharging, mill
- explosion hazard area
- · bellows, compensators
- screening machine/ sifting machine, vibration screening machine, tumbler screening machine, plansifter, windsifter

## **Properties**

- · highly flexible
- abrasion-resistant
- · vibration resistant

- Food grade wall, complies with: EU-Directive 10/2011, EC 1935/2004 and EU 2015/174, FDA 21 CFR 177.2600
- · odorless and tasteless
- · microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
  patented PROTAPE® tape hose
- · very good low temperature flexibility
- Permanently antistatic wall according to ISO 8031 electrical and surface resistance  $< 10^9 \,\Omega$ (according to NFPA 652 108-109 Ω)
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dust (zone 22 inside), for conveying of non-flammable liquids, for use • further diameters and lengths available on in zone 1 and 2 (gases)
- · manufacturing process acc. GMP EC 2023/2006
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Temperature range

- -40°F to 195°F
- short time to 255°F

#### Design

- wall interior and exterior smooth
- · wall: permanently antistatic premium etherpolyurethane (Pre-PUR®)
- wall thickness 0.04 approx.
- grounding wire

#### **Delivery variants**

- request
- transparent (standard)
- · customer-specific branding

I.D.	outer Ø	Pressure	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(psi)	(lb/ft)	(ft)	(ft)	
2 / 50-51	2.165	8.412	0.208	6	-	335-0050-0000
2,36 / 60	2.559	8.122	0.249	6	-	335-0060-0000
- / 80	3.346	7.397	0.316	16	8	335-0080-0000
- / 85	3.543	6.962	0.336	16	8	335-0085-0000
4 / 100-102	4.134	5.947	0.397	16	8	335-0100-0000
-/110	4.528	5.439	0.437	16	8	335-0110-0000
4,5 / 114-115	4.724	5.149	0.450	-	8 16	335-0115-0000
4,72 / 120	4.921	4.931	0.470	16	8	335-0120-0000
5 / 125-127	5.118	4.786	0.491	16	8	335-0125-0000
6 / 150-152	6.102	3.989	0.591	16	8	335-0150-0000
- / 155	6.299	3.844	0.605	16	8	335-0155-0000
6,3 / 160	6.496	3.699	0.625	-	8 16	335-0160-0000
6,5 / 165	6.693	3.626	0.645	16	8	335-0165-0000
7 / 178-180	7.283	3.336	0.706	16	8	335-0180-0000
8 / 200-203	8.071	2.973	0.766	16	8	335-0200-0000
- / 205	8.268	2.901	0.800	16	8	335-0205-0000
- / 220	8.858	2.683	0.860	-	8 16	335-0220-0000
- / 250	10.039	2.393	0.974	16	8	335-0250-0000
- / 275	11.024	2.176	1.069	16	8	335-0275-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate was not the gredient. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

# PROTAPE® PUR-C 335 FOOD-AS FLAT















I.D.	outer Ø	Pressure	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(psi)	(lb/ft)	(ft)	(ft)	
12 / 305	12.205	1.958	1.190	16	8	335-0305-0000
-/350	13.976	1.668	1.364	-	8 16	335-0350-0000
16 / 405-406	16.142	1.523	1.573	16	8	335-0405-0000

## Accessories









**CONNECT 270-271** 

CLAMP 208

**CONNECT 228**