# AIRDUC® PUR 355 SWEEPER REINFORCED


















Sweeper hose, heavy and reinforced, interior folds

# **Applications**

• municipal vehicle: sweeper, sweeping machine

### **Properties**

- · heavy duty and reinforced
- highly abrasion resistant
- · microbe resistant
- REACH according to --> Technology / Technical Information / REACH
- very good low temperature flexibility
- conforms to RoHS guideline

## **Temperature Range**

• -40°C to 90°C

#### Design

- AIRDUC® profile hose
- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 1,5 to 1,8 mm approx.
- reinforcement of the primary abrasion areas

#### **Delivery variants**

- further diameters and lengths available on request
- transparent (standard)
- special colours: transparent, partially coloured, completely coloured
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
8 / 200-203	215.00	0,365	0,125	178.00	2.65	-	5	355-0203-5015

# Accessories



CONNECT 240 + 241 AS



CLAMP 211



**CONNECT 270-271**