# AIRDUC® PUR 355 SWEEPER




















Sweeper hose, heavy duty, exterior folds, very flexible

### **Applications**

• municipal vehicle: sweeper, sweeping machine

#### **Properties**

- · heavy duty
- highly flexible + compressible
- highly abrasion resistant
- · protected, flow-optimizing exterior folds
- microbe resistant

- · very good low temperature flexibility
- according to DIN 26057 Type 3
- REACH according to --> Technology / Technical Information / REACH
- · conforms to RoHS guideline

#### Temperature range

• -40°F to 195°F

#### Design

AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 0.055 to 0.06 in approx.

#### **Delivery variants**

- further diameters and lengths available on request
- transparent + partially black colored (standard)
- special colors: transparent, partially colored, completely colored
- · customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
partially black colored								
6,3 / 160	6.811	5.729	5.758	7.874	1.613	-	12 25	355-0160-5200
7 / 178-180	7.598	5.584	4.872	10.236	1.815	-	12 25	355-0180-5200
8 / 203	8.504	5.323	3.691	12.992	2.124	12 25	-	355-0203-5200
- / 206	8.622	5.294	3.544	13.189	2.157	-	12 25	355-0206-5200
- / 208	8.701	5.221	3.396	13.307	2.184	-	12 25	355-0208-5200
- / 225	9.370	4.859	2.953	14.331	2.352	-	5 10	355-0225-5200
10 / 254	10.512	4.134	2.362	16.024	2.641	12 25	-	355-0254-5200
- / 257	10.630	4.206	2.215	16.220	2.675	-	12 25	355-0257-5200
- / 275	11.339	3.916	2.067	17.283	2.856	-	12 25	355-0275-5200

## **Accessories**



**CONNECT 240 + 241 AS** 



CLAMP 211



**CONNECT 270-271**