


# AIRDUC® PUR 355 VAC-TRUCK ORANGE



Vacuum truck hose, heavy and reinforced, very flexible

## Applications

- suction excavator
- municipal vehicle: sweeper, sweeping machine

## Properties

- heavy duty and reinforced
- highly abrasion resistant
- microbe resistant
- good resistance to oil, gasoline and chemicals

- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Temperature Range

- -40 °C to 90 °C
- short time to 125 °C

## Design

- AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 2,5 mm approx.
- reinforcement of the primary abrasion areas

## Delivery variants

- further diameters and lengths available on request
- orange (standard)
- special colours: transparent, full coloured
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
8 / 200-203	213.00	0,600	0,120	316.00	5.13	-	5	355-0200-5202

## Accessories



CONNECT 240 + 241 AS



CONNECT 270-271



CLAMP 211

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).