



Vacuum truck hose, heavy duty and reinforced, very flexible

## Applications

- suction excavator
- municipal vehicle: sweeper, sweeping machine

## Properties

- heavy duty and reinforced
- highly abrasion resistant
- microbe resistant
- good resistance to oil, gasoline, and chemicals

- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Temperature range

- -40 °F to 195 °F
- short time to 255 °F

## Design

- AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 0.10 in approx.
- reinforcement of the primary abrasion areas

## Delivery variants

- further diameters and lengths available on request
- orange (standard)
- special colors: transparent, full colored
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
8 / 200-203	8.386	8.702	3.544	12.441	3.448	12 25	-	355-0200-5202

## Accessories



CLAMP 211



CONNECT 270-271



CONNECT 240 + 241 AS