


AIRDUC® PUR 356 EC (XHD)



Electrically conductive polyurethane hose, super-heavy duty

Applications

- hose/ ducting for high throughput of extremely abrasive bulk material, granulate and stone
- vacuum truck, suction vehicle, dry suction truck: industrial cleaning, furnace cleaning
- explosion hazard area
- Coal mine, mine, tunnelling: ventilation, methane extraction
- raw material conveying hose for powders, granulates, sand, quartz, gravel, shards and chips/ shavings
- silo, silo vehicle/ silo truck, tanker/ tank truck: silo charging, silo discharging

Properties

- super-heavy duty
- extremely abrasion-resistant with reinforcement underneath wire and narrow hose pitch

- good resistance to oil, gasoline, and chemicals
- very good low temperature flexibility
- electrically conductive wall: electrical and surface resistance $<10^3 \Omega$ (according to NFPA 652 $<10^6 \Omega$)
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: pneumatic transport of flammable dusts and bulk materials (Zone 20, 21, 22 inside), aspiration of combustible dusts (Zone 22 inside),
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: for conveying for flammable liquids (inside zone 0, 1, 2), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in zone 0 (gases)
- according to DIN 26057 Type 4
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -40°F to 195°F

Design

- AIRDUC® profile hose
- spring steel wire firmly embedded in wall
- wall: electrically conductive premium ester-polyurethane (Pre-PUR®)
- wall thickness 0.08 to 0.10 in approx.
- reinforcement of the primary abrasion areas

Delivery variants


- further diameters and lengths available on request
- black (standard)
- customer-specific branding

| I.D. | outer Ø | Pressure | Vacuum | Bending radius | Weight | Dimensions in Stock | Production lengths | Order No. |
|-------------|---------|----------|--------|----------------|---------|---------------------|--------------------|---------------|
| (in / mm) | (in) | (psi) | (inHG) | (in) | (lb/ft) | (ft) | (ft) | |
| - / 40 | 2.008 | 52.722 | 29.530 | 4.291 | 0.551 | - | 25 50 | 356-0040-1003 |
| - / 50 | 2.402 | 42.787 | 29.530 | 5.276 | 0.672 | - | 25 50 | 356-0050-1003 |
| 2 / 50-51 | 2.441 | 40.611 | 29.530 | 5.276 | 0.679 | 25 50 | - | 356-0051-1003 |
| 2,36 / 60 | 2.795 | 36.042 | 29.530 | 6.142 | 0.793 | - | 25 50 | 356-0060-1003 |
| 2,5 / 63-65 | 2.913 | 34.737 | 29.530 | 6.417 | 0.833 | 25 50 | - | 356-0063-1003 |
| - / 65 | 2.992 | 33.432 | 29.530 | 6.654 | 0.853 | - | 25 50 | 356-0065-1003 |
| - / 70 | 3.228 | 31.111 | 29.530 | 7.323 | 0.921 | - | 25 50 | 356-0070-1003 |
| - / 75 | 3.425 | 29.153 | 29.530 | 7.677 | 0.981 | - | 25 50 | 356-0075-1003 |
| 3 / 76 | 3.465 | 28.935 | 29.530 | 7.677 | 0.995 | 25 50 | - | 356-0076-1003 |
| - / 80 | 3.622 | 27.413 | 29.530 | 8.071 | 1.042 | - | 25 50 | 356-0080-1003 |
| - / 100 | 4.449 | 24.439 | 29.530 | 10.709 | 1.526 | - | 25 50 | 356-0100-1003 |
| 4 / 102 | 4.528 | 24.004 | 29.530 | 10.709 | 1.552 | 25 50 | - | 356-0102-1003 |


Accessories

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

AIRDUC® PUR 356 EC (XHD)



CONNECT 245



CONNECT 242



CONNECT MOULD ASSEMBLY 233



CONNECT SAFETY CLAMP ASSEMBLY 231



CONNECT 228




CONNECT 243




CONNECT PRESS ASSEMBLY 232



CONNECT THREAD FITTING 234



CONNECT 244



CONNECT 240 + 241 AS



CLAMP 216



CLAMP 211



CONNECT 246 AS



CONNECT 240 EC