


PROTAPE® ALU-PES 369 SE



Aluminium/Polyester air conditioning hose, flame resistant (M0)

Applications

- flexible hose/ ducting for gases
- Air conditioning in marine applications

Properties

- super-light weight
- highly flexible + compressible 10:1

- Flame-retardant wall according to C.S.T.B. class M0 (France)
- Flame-retardant according to: non-combustible according to BUREAU VERITAS standards (France)
- conforms to RoHS guideline

Temperature range

- 22°F to 482°F

Design


- PROTAPE® tape hose
- spring steel wire integrated in wall
- fabric-reinforced tape; wall: aluminum coated fabric
- Pressure max. 300 mm H2O
- Air speed max. 30 m/s

Delivery variants

- further diameters and lengths available on request
- silver

I.D.	outer Ø	Bending radius	Weight	Production lengths	Order No.
(in / mm)	(in)	(in)	(lb/ft)	(ft)	
3 / 75-76	3.055	2.402	0.000	25	369-0076-3507
- / 82	3.345	2.598	0.000	25	369-0082-3507
4 / 100-102	4.134	3.228	0.000	25	369-0102-3507
5 / 125-127	5.118	4.016	0.000	25	369-0127-3507
6 / 150-152	6.117	4.803	0.000	25	369-0152-3507
6,3 / 160	6.433	5.039	0.000	25	369-0160-3507
7 / 178-180	7.220	5.669	0.000	25	369-0180-3507
8 / 200-203	8.126	6.378	0.000	25	369-0203-3507
10 / 254	10.134	7.992	0.000	25	369-0254-3507
12 / 305	12.024	9.606	0.000	25	369-0305-3507
- / 315	12.535	9.921	0.000	25	-
14 / 356	14.150	11.220	0.000	25	369-0356-3507
16 / 405-406	16.118	12.795	0.000	25	369-0406-3507
18 / 457	18.156	14.409	0.000	25	369-0457-3507
20 / 508	20.165	15.984	0.000	25	369-0508-3507
24 / 610	24.181	19.213	0.000	25	369-0610-3507

Accessories



CLAMP 210 BRIDGE CLAMP



CONNECT 270-271



CLAMP 208



CONNECT 228

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.