



Vacuum cleaner hose, electrically
conductive $<10^6 \Omega$

Applications

- flexible hose/ ducting for gases and for dust, powder, fibres
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- swimming pool cleaning
- scrubber, floor cleaning machine

Properties

- lightweight

- highly flexible
- crush resistant
- floatable
- good resistance to alkalis and acids
- surface resistance $<10^6 \Omega$
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dusts (Zone 22 inside), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in Zone 0 (gases)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- 25 °C to 65 °C

Design

- EVA design
- self-supporting profile design
- open profile geometry
- wall: EVA

Delivery variants

- further diameters and lengths available on request
- black (standard)

I.D.	outer Ø	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(mm)	(kg/m)	(m)	(m)	
1 / 25	32.20	0,500	54.00	0.15	30	-	373-0025-1003
1,25 / 32	40.40	0,500	66.00	0.24	30	-	373-0032-1003
1,5 / 38	47.20	0,500	74.00	0.31	30	-	373-0038-1003
- / 40	49.40	0,500	80.00	0.32	30	-	373-0040-1003
2 / 50-51	59.00	0,500	97.00	0.44	30	-	373-0050-1003

Accessories



CONNECT 227



CLAMP 208



CONNECT 228