



Vacuum cleaner hose, electrically conductive $<10^6 \Omega$

Applications

- flexible hose/ ducting for gases and for dust, powder, fibers
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- swimming pool cleaning
- scrubber, floor cleaning machine

Properties

- lightweight

- highly flexible
- crush resistant
- floatable
- good resistance to alkalis and acids
- surface resistance $<10^6 \Omega$
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- 15°F to 150°F

Design

- EVA design
- self-supporting profile design
- open profile geometry
- wall: EVA

Delivery variants

- further diameters and lengths available on request
- black (standard)

I.D.	outer Ø	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
1 / 25	1.268	14.765	2.126	0.101	100	-	373-0025-1003
1,25 / 32	1.591	14.765	2.598	0.161	100	-	373-0032-1003
1,5 / 38	1.858	14.765	2.913	0.208	100	-	373-0038-1003
- / 40	1.945	14.765	3.150	0.215	100	-	373-0040-1003
2 / 50-51	2.323	14.765	3.819	0.296	100	-	373-0050-1003

Accessories



CONNECT 228



CLAMP 208



CONNECT 227