



# METAL HOSE 375



Metal hose, suction hose (up to +120 °C)

## Applications

- hose/ ducting for high volume of abrasive powder, bulk material, granulate and for gases
- extraction unit, dedusting system, filter system, oil mist extraction
- explosion hazard area
- wood dust extraction, wood chips: furniture production, saw mill
- paper mill, paper and pulp industry, packaging machine: edge strip suctioning system/ edge trim exhaust systems
- high temperature extraction: oven, foundry, furnace, smelting, ceramics industry, glass industry, steel plant, aluminium mill

## Properties

- abrasion-resistant
- electrically conductive wall: electrical and surface resistance  $<10^3 \Omega$  (according to NFPA 652  $<10^6 \Omega$ )
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: pneumatic transport of flammable dusts and bulk materials (Zone 20, 21, 22 inside)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Temperature Range

- up to 120 °C

## Design

- Metal hose
- profiled metal strip, galvanised steel
- hooked profile
- seal: special fibre

## Delivery variants

- further diameters and lengths available on request
- without sealing or with rubber sealing

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
- / 20	24.00	90.00	0.34	-	2,5 5 10	375-0020-0000
1 / 25	29.00	98.00	0.42	2,5 5 10	-	375-0025-0000
- / 30	34.00	115.00	0.50	-	2,5 5 10	375-0030-0000
1,25 / 32	36.00	124.00	0.53	2,5 5 10	-	375-0032-0000
1,36 / 35	39.00	133.00	0.58	2,5 5 10	-	375-0035-0000
1,5 / 38	42.00	136.00	0.63	-	2,5 5 10	375-0038-0000
- / 40	45.00	135.00	0.70	2,5 5 10	-	375-0040-0000
1,75 / 44-45	50.00	143.00	0.74	-	2,5 5 10	375-0045-0000
2 / 50-51	55.00	155.00	0.81	2,5 5 10	-	375-0050-0000
- / 55	60.00	173.00	0.90	-	2,5 5 10	375-0055-0000
2,36 / 60	66.00	185.00	1.01	2,5 5 10	-	375-0060-0000
2,5 / 63-65	71.00	198.00	1.09	2,5 5 10	-	375-0065-0000
- / 70	76.00	205.00	1.17	2,5 5 10	-	375-0070-0000
3 / 75-76	81.00	218.00	1.25	2,5 5 10	-	375-0075-0000
- / 80	86.00	230.00	1.33	2,5 5 10	-	375-0080-0000
3,5 / 89-90	97.00	235.00	1.78	-	2,5 5 10	375-0090-0000
4 / 100-102	107.00	250.00	1.98	2,5 5 10	-	375-0100-0000
- / 110	117.00	275.00	2.17	-	2,5 5 10	375-0110-0000
4,72 / 120	127.00	320.00	2.36	2,5 5 10	-	375-0120-0000
5 / 125-127	132.00	338.00	2.45	2,5 5 10	-	375-0125-0000
- / 130	139.00	345.00	2.86	2,5 5 10	-	375-0130-0000
5,5 / 140	149.00	360.00	3.07	2,5 5 10	-	375-0140-0000
6 / 150-152	159.00	385.00	3.29	2,5 5 10	-	375-0150-0000
6,3 / 160	169.00	410.00	3.50	2,5 5 10	-	375-0160-0000
- / 170	179.00	435.00	3.72	-	2,5 5 10	375-0170-0000
7 / 178-180	189.00	455.00	3.93	2,5 5 10	-	375-0180-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).


## METAL HOSE 375

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
8 / 200-203	211.00	460.00	5.22	<b>2.5 5 10</b>	-	375-0200-0000
- / 225	236.00	518.00	5.86	<b>2.5 5 10</b>	-	375-0225-0000
- / 250	261.00	575.00	6.50	<b>2.5 5</b>	-	375-0250-0000
- / 275	286.00	633.00	7.13	<b>2.5 5</b>	-	375-0275-0000
- / 300	311.00	700.00	7.78	<b>2.5 5</b>	-	375-0300-0000

### Accessories




CONNECT 270-271




CONNECT 202



CONNECT 206



CONNECT 203-204



CONNECT 205

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).