



PVC hose, heavy, flexible at low temp.
(down to -25 °C)

Applications

- flexible hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- suction vehicle: sewer cleaning, sewage cleaning
- agricultural industry: irrigation, fertilizers, insecticides
- agricultural industry: manure spreader, slurry spreader, slurry tanker
- agricultural industry, conveying of seed and fertilizers: seeding machine, seed drill, drilling machine
- caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel, yachts: sanitary installation, water supply
- silos and tankers: silo charging, silo discharging
- silo and tankers: conveying of wood pellets, plastic granulate, plastic powder

Properties

- heavy duty
- good resistance to alkalis and acids
- good resistance to chemicals
- UV stabilized
- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -25 °C to 60 °C

Design

- NORPLAST® full plastic hose
- hard plastic spiral integrated in wall
- spiral: rigid PVC
- smooth interior
- wall: low temperature flexible soft PVC

Delivery variants

- further diameters and lengths available on request
- green-transparent (standard)
- special colours: coloured spiral, full coloured
- customer-specific branding

Accessories



CLAMP 211