













Antistatic polyurethane hose, heavy duty, grounding wire

Applications

- flexible hose/ ducting for abrasive powder, bulk material, granulate and for gases
- · food industry, pharmaceutical industry: food, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses
- mixer, dryer, packaging machine, bulk-bag (big bag)-charging and discharging, mill
- · plastic industry, conveying of granulates and powders: granulate conveying equipment, vacuum hopper/ conveyor, suction conveyor, dosing system, bulk-bag (big bag)-charging and discharging, shredder, mill, extruder, injection moulding machine
- silo, silo vehicle/ silo truck, tanker/ tank truck: silo charging, silo discharging
- silo, silo vehicle/ silo truck, tanker/ tank truck: conveying of wood pellets, plastic granulate, plastic powder
- silo, silo vehicle/ silo truck, tanker/ tank truck: conveying of e.g. rice, dry food, cereals, sugar, milk powder, powders, coffee, tea, grains, flour, frozen foods

Properties

super-heavy duty

- · abrasion-resistant
- increased pressure and vacuum resistance
- Food grade wall, complies with: EU-Directive 10/2011, EC 1935/2004 and EU 2015/174, FDA 21 CFR 177.2600
- microbe and hydrolysis resistant
- · phthalate-free
- Grounding wire for discharging of electrostatic charging
- · electrical and surface resistance of the inliner <109
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dust (zone 22 inside), • grounding wire (carbon + polyester + copper) for conveying of non-flammable liquids, for use in zone 1 and 2 (gases)
- · manufacturing process acc. GMP EC 2023/2006
- · conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5°F to 160°F
- short time to 175°F

Design

- NORPLAST® full plastic hose
- · hard plastic spiral integrated in wall
- spiral: rigid PVC
- smooth interior
- wall: special premium ether-polyurethane (Pre-
- Wall: antistatic polyurethane inside layer 0,7mm - 1,0 mm approx., exterior soft PVC

Delivery variants

- transparent (standard)
- · special colors: colored spiral, full colored
- · customer-specific branding

Accessories



CI AMP 211



CONNECT 270-271



CONNECT STORZ DIN ALU 251



254



CONNECT KARDAN CONNECT MOULD **ASSEMBLY 233**



CONNECT KAMLOK ALU 253