



Polyurethane hose, extremely heavy duty

Applications

- hose/ ducting for high throughput of extremely abrasive bulk material, granulate and stone
- vacuum truck, suction vehicle, dry suction truck: industrial cleaning, furnace cleaning
- suction vehicles: roof gravelling, roof gravel conveying
- animal stall, animal shed: feedstuff conveying, feedstuff plant, animal feed transport
- raw material conveying hose for powders, granulates, sand, quartz, gravel, shards and chips/ shavings
- silo, silo vehicle/ silo truck, tanker/ tank truck: silo charging, silo discharging
- silo, silo vehicle/ silo truck, tanker/ tank truck: conveying of wood pellets, plastic granulate, plastic powder

Properties

- external abrasion protection via external helix (saves floor space, prolong service life, easy to use)

- extremely heavy duty
- extremely abrasion resistant
- very high pressure, vacuum and compression resistance
- good resistance to chemicals
- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5 °F to 160 °F
- short time to 175 °F

Design

- NORPLAST® full plastic hose
- hard plastic spiral integrated in wall
- spiral: rigid PVC
- smooth interior
- wall: interior premium polyurethane layer, 2,0 mm approx. exterior soft PVC

Delivery variants

- further diameters and lengths available on request
- blue inner liner, transparent exterior wall (standard)
- special colors: colored spiral, full colored
- customer-specific branding

Accessories



CLAMP 211



CONNECT KARDAN 254



CONNECT KAMLOK ALU 253



CONNECT TANK TRUCK BRASS 252



CONNECT STORZ DIN ALU 251