



PVC hose, super-heavy, flexible at low temp. (down to -40 °C)

## Applications

- hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- suction vehicle: sewer cleaning, sewage cleaning
- vacuum truck, suction vehicle, dry suction truck: industrial cleaning, furnace cleaning
- airport, airplane, rail vehicle, train, railway, boat, ship/ vessel, yacht: toilet discharging/ disposal
- agricultural industry: irrigation, fertilizers, insecticides
- agricultural industry: manure spreader, slurry spreader, slurry tanker

## Properties

- external abrasion protection via external helix (protects floors and surfaces, prolongs service life, easy to use)

- super-heavy duty
- very high pressure, vacuum and compression resistance
- good resistance to alkalis and acids
- good resistance to chemicals
- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Temperature Range

- -40 °C to 60 °C

## Design

- NORPLAST® full plastic hose
- outer hard plastic spiral
- spiral: impact-resistant modified rigid PVC
- smooth interior
- wall: high grade soft PVC

## Delivery variants

- further diameters and lengths available on request
- grey and blue partially coloured (standard)
- special colours: coloured spiral, full coloured
- customer-specific branding

## Accessories



CONNECT 270-271



CLAMP 211