



PVC hose, super-heavy duty, flexible at low temp. (down to -13°F)

Applications

- hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- suction vehicle: sewer cleaning, sewage cleaning
- vacuum truck, suction vehicle, dry suction truck: industrial cleaning, furnace cleaning
- airport, airplane, rail vehicle, train, railway, boat, ship/ vessel, yacht: lavatory waste
- agricultural industry: irrigation, fertilizers, insecticides
- agricultural industry: manure spreader, slurry spreader, slurry tanker
- silo, silo vehicle/ silo truck, tanker/ tank truck: silo charging, silo discharging
- silo, silo vehicle/ silo truck, tanker/ tank truck: conveying of wood pellets, plastic granulate, plastic powder

Properties

- external abrasion protection via external helix (saves floor space, prolong service life, easy to use)
- super-heavy duty
- very high pressure, vacuum and compression resistance
- good resistance to alkalis and acids
- good resistance to chemicals
- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -15°F to 140°F

Design

- NORPLAST® full plastic hose
- outer hard plastic spiral
- abrasion resistant protection profile (wear strip)
- spiral: rigid PVC
- smooth interior
- wall: high grade low temperature flexible soft PVC

Delivery variants

- further diameters and lengths available on request
- gray and blue partially colored (standard)
- special colors: colored spiral, full colored
- customer-specific branding

Accessories



CLAMP 211



CONNECT KAMLOK ALU 253



CONNECT 270-271



CONNECT KARDAN 254