


NORFLEX® PVC 400



PVC hose

Applications

- flexible hose/ ducting for liquids and for gases
- hose/ tubing pump
- industrial washing machine: washing water hose
- compressed air hose, cooling water hose, water hose
- heating hose: interior hose for media transfer

Properties

- highly flexible

- crush resistant
- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5°F to 140°F

Design

- NORFLEX® design
- wall interior and exterior smooth
- wall: soft PVC

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colors: full colored
- customer-specific branding

I.D. (in / mm)	outer Ø (in)	Wall thickness (in)	Weight (lb/ft)	Dimensions in Stock (ft)	Order No.
- / 2	0.157	0.039	0.007	300	400-9020-0000
1/8 / 3	0.197	0.039	0.013	300	400-9030-0000
- / 4	0.236	0.039	0.013	300	400-9040-0000
- / 4	0.276	0.059	0.020	300	400-9040-2182
- / 5	0.315	0.059	0.027	300	400-9050-0000
1/4 / 6	0.354	0.059	0.034	300	400-9060-0000
1/4 / 6	0.394	0.079	0.047	300	400-9060-2184
- / 7	0.394	0.059	0.034	300	400-9070-0000
5/16 / 8	0.472	0.079	0.054	150	400-9080-0000
- / 9	0.512	0.079	0.060	150	400-9090-0000
3/8 / 10	0.551	0.079	0.067	150	400-9100-0000
- / 12	0.669	0.098	0.101	150	400-9120-0000
- / 14	0.748	0.098	0.114	150	400-9140-0000
- / 15	0.787	0.098	0.121	150	400-9150-0000
5/8 / 16	0.866	0.118	0.155	150	400-9160-0000
- / 18	0.945	0.118	0.175	150	400-9180-0000
- / 20	0.945	0.079	0.121	150	400-9200-0000
- / 20	1.024	0.118	0.188	150	400-9200-2175
7/8 / 22	1.102	0.118	0.208	150	400-9220-0000
1 / 25	1.220	0.118	0.228	75	400-9250-0000
1 1/8 / 30	1.457	0.138	0.323	75	400-9300-0000
- / 40	1.890	0.157	0.484	75	400-9400-0000
2 3/8 / 60	2.756	0.197	0.894	75	400-9600-0000

Accessories

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

NORFLEX® PVC 400



CLAMP 208

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.