



Layflat PVC water hose

Applications

- Use as sprinkler hose in agriculture and gardening
- Suitable for water treatment on construction sites and in industry

Properties

- consists of one piece and is therefore less vulnerable to mechanical damage and leakage is reduced to a minimum
- according to the norm EN ISO 1307:2008

Temperature Range

• -20°C to 60°C

Design

- PVC inner layer
- PVC outer layer

Delivery variants

• blue inner tube, blue exterior wall

I.D.	outer Ø	Wall Thickness	Hose flat measured	Operating pressure (20°C)	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(mm)	(mm)	(bar)	(kg/m)	(m)	
1 / 25	29.00	2.00	39,00	7,000	0.18	50	4010-025-000
1,25 / 32	36.00	2.00	50,00	7,000	0.21	100	4010-032-000
1,5 / 38	42.00	2.00	60,00	7,000	0.24	100	4010-038-000
2/51	55.00	2.00	82,00	7,000	0.35	100	4010-050-000
2,5 / 63	67.00	2.00	99,00	7,000	0.45	100	4010-063-000
3 / 76	80.00	2.00	118,00	6,000	0.61	100	4010-075-000
4 / 102	106.00	2.00	160,00	6,000	0.92	100	4010-100-000
5 / 127	131.00	2.00	196,00	6,000	1.15	50	4010-125-000
6 / 152	156.00	2.00	239,00	6,000	1.57	50	4010-150-000
8 / 203	207.00	2.00	319,00	4,000	2.15	50	4010-200-000