



PTFE hose/ tubing

Applications

- flexible hose/ ducting for liquids and for gases
- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- heating hose: interior hose for media transfer

Properties

- highly flexible
- food grade wall, complies with: FDA 21 CFR Part 177.1550, German guideline XV BfR

- odourless and tasteless
- anti-adhesive
- microbe and hydrolysis resistant
- good resistance to alkalis and acids
- extremely good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -150°C to 200°C

Design

- NORFLEX® design
- wall interior and exterior smooth
- wall: PTFE

Delivery variants

- further diameters and lengths available on request
- transparent (standard)

I.D.	outer Ø	Wall Thickness	Pressure	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(mm)	(bar)	(kg/m)	(m)	
- / 2	4.00	1.00	15,000	0.01	50	407-9020-0000
1/8 / 3	5.00	1.00	15,000	0.01	50	407-9030-0000
- / 4	6.00	1.00	10,000	0.02	50	407-9040-0000
1/4 / 6	8.00	1.00	10,000	0.02	50	407-9060-0000
5/16 / 8	10.00	1.00	5,000	0.03	50	407-9080-0000
3/8 / 10	12.00	1.00	5,000	0.04	50	407-9100-0000
- / 12	14.00	1.00	5,000	0.04	50	407-9120-0000
- / 14	16.00	1.00	5,000	0.05	50	407-9140-0000

Accessories



CLAMP 208