



Silicone hose

Applications

- flexible hose/ ducting for liquids and for gases
- food industry, pharmaceutical industry: food, pharmaceutical
- hose/ tubing pump
- heating hose: interior hose for media transfer

Properties

- highly flexible
- crush resistant
- food grade wall, complies with: FDA 21 CFR 177.2600, German guideline XV BfR
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- 75 °F to 355 °F

Design

- NORFLEX® design
- wall interior and exterior smooth
- wall: silicone 60 ± 5 Shore A

Delivery variants

- further diameters and lengths available on request
- transparent (standard)

I.D.	outer Ø	Wall thickness	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(in)	(lb/ft)	(ft)	(ft)	
- / 2	0.157	0.039	0.007	-	150	408-9020-0000
- / 2	0.236	0.079	0.020	-	150	408-9020-2163
1/8 / 3	0.197	0.039	0.013	-	150	408-9030-0000
1/8 / 3	0.276	0.079	0.027	-	150	408-9030-2163
1/8 / 3	0.236	0.059	0.020	150	-	408-9030-2182
- / 4	0.236	0.039	0.013	-	150	408-9040-0000
- / 4	0.315	0.079	0.034	-	150	408-9040-2163
- / 4	0.276	0.059	0.020	150	-	408-9040-2182
- / 5	0.276	0.039	0.013	-	150	408-9050-0000
- / 5	0.315	0.059	0.027	-	150	408-9050-2182
1/4 / 6	0.354	0.059	0.027	-	150	408-9060-0000
1/4 / 6	0.394	0.079	0.040	150	-	408-9060-2163
- / 7	0.394	0.059	0.034	-	150	408-9070-0000
5/16 / 8	0.394	0.039	0.020	-	150	408-9080-0000
5/16 / 8	0.472	0.079	0.047	150	-	408-9080-2163
5/16 / 8	0.551	0.118	0.074	-	150	408-9080-2175
- / 9	0.512	0.079	0.054	-	150	408-9090-0000
3/8 / 10	0.551	0.079	0.060	-	150	408-9100-0000
3/8 / 10	0.591	0.098	0.074	150	-	408-9100-2174
- / 12	0.630	0.079	0.067	-	150	408-9120-0000
- / 12	0.709	0.118	0.114	-	75	408-9120-2175

Accessories



CLAMP 208