

NORPLAST® PVC COSMO® ELASTICO SEEDER



Supply hose for seed and solid fertilizers

Applications

- specially designed for use in the agricultural industry

Properties

- extremely kink-resistant and dimensionally stable
- UV and ozone resistant

- Vacuum up to 0.6 bar

Temperature range

- 5°F to 140°F

Design

- PVC inner layer

- outer layer made of soft PVC
- outer layer smooth
- rigid PVC spiral

Delivery variants

- transparent inner tube, transparent exterior wall, anthracite spiral

I.D.	outer Ø	Bending radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(in)	(in)	(lb/ft)	(ft)	
- / 30	1.386	4.724	0.228	50	4406-030-000
1,25 / 32	1.472	5.118	0.249	50	4406-032-000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.