NORFLEX® PUR 441 ROBOTIC
















Abrasion resistant polyurethane hose/ tubing for industrial robots, fabric reinforced high pressure hose

Applications

- flexible hose/ ducting for liquids and for gases and for abrasive solids
- injection moulding tool cooling, cooling water supply
- agricultural industry: high pressure spraying hose e.g. for pesticides
- compressed air hose, cooling water hose, water hose
- fabric reinforced hose/ braided hose
- industrial robot, robotic, welding equipment, welding robot, welding gun: welding spot resistant hose, hose for dresspack for media as water and air
- heating hose: interior hose for media transfer

• conforms to RoHS guideline

• highly abrasion resistant

REACH according to --> Technology /
Technical Information / REACH

• good resistance to oil, gasoline and chemicals

Temperature Range

• -35°C to 80°C

crush resistant

Design

- NORFLEX[®] design
- fabric reinforced wall
- smooth interior and exterior

 wall: special premium polyurethane (Pre-PUR[®])

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- grey (standard)
- black (standard)
- blue (standard)
- red (standard)
- yellow (standard)
- green (standard)
- · special colours: full coloured
- customer-specific branding

Properties

- fabric reinforced
- highly flexible

I.D.	outer Ø	Pressure	Burst Pressure	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
				blue				
3/8 / 9,2	16.00	20,000	80	55.00	0.15	50	-	441-9094-0400
1/2 / 12,5	19.50	20,000	80	69.00	0.23	50	-	441-9128-0400
3/4 / 19,5	28.50	20,000	50	140.00	0.41	50	-	441-9190-0400
				black				
3/8 / 9,2	16.00	20,000	80	55.00	0.15	50	-	441-9094-0402
1/2 / 12,5	19.50	20,000	80	69.00	0.23	50	-	441-9128-0402
				red				
3/8 / 9,2	16.00	20,000	80	55.00	0.15	50	-	441-9094-0403
1/2 / 12,5	19.50	20,000	80	69.00	0.23	50	-	441-9128-0403
3/4 / 19,5	28.50	20,000	50	140.00	0.41	50	-	441-9190-0403
				green				
3/8 / 9,2	16.00	20,000	80	55.00	0.15	50	-	441-9094-0404
1/2 / 12,5	19.50	20,000	80	69.00	0.23	50	-	441-9128-0404
3/4 / 19,5	28.50	20,000	50	140.00	0.41	50	-	441-9190-0404

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.

www.norres.com 1

NORFLEX® PUR 441 ROBOTIC











Accessories



CLAMP 208