
NORPLAST® 4460 QUADRIFLEX







Thermoplastic suction hose

Applications

- for industrial water, wastewater and dung
- Has been used to full satisfaction in the public sector and in agriculture for years
- Due to its smooth outer wall, very suitable for use in water treatment plants, water reservoirs, slurry pits, etc.

Properties

· Has an oval spiral instead of a round one

- according to the norm EN ISO 1307:2008
- Vacuum up to 0.9 bar

Temperature Range

• -25°C to 60°C

Design

• soft PVC inner layer

- PVC outer layer
- smooth construction cover
- rigid PVC spiral
- smooth inner tube

Delivery variants

• orange inner tube, orange exterior wall, anthracite spiral (standard)

I.D.	outer Ø	Wall Thickness	Bending Radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(mm)	(mm)	(kg/m)	(m)	
2 / 50-51	60.00	4.50	204.00	0.95	50	4460-050-000
3 / 75-76	86.00	5.00	304.00	1.60	50	4460-075-000
- / 80	90.00	5.00	320.00	1.70	50	4460-080-000
3,5 / 89-90	100.00	5.00	360.00	1.95	50	4460-090-000
4 / 100-102	114.00	6.00	408.00	2.42	50	4460-100-000
- / 110	121.00	5.50	440.00	2.60	30	4460-110-000
5 / 125-127	140.00	6.50	508.00	3.30	20	4460-125-000
6 / 150-152	167.00	7.50	608.00	4.40	4 5 20	4460-150-000