


CP HYP 450



Clamp profile hose (clip hose), (up to +338 °F)

Applications

- flexible hose/ ducting for hot and cold gases and for dust, powder, fibers
- chemical industry: chemical vapors, vapor return hose at loading arm, paint steam, spray mist extraction
- industrial washing machine: air blower hose for drying
- high temperature extraction: oven, foundry, furnace, smelting, ceramics industry, glass industry, steel plant, aluminium mill
- bellows, compensators

Properties

- abrasion protection via external clamp profile

- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- vibration resistant
- very good heat resistance
- good resistance to oil, gasoline, and chemicals
- good resistance to alkalis and acids
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- 40 °F to 340 °F

Design

- CP construction
- Clamp profile supporting spiral: galvanised steel
- wall: CSM coated polyester fabric

Delivery variants

- further diameters and lengths available on request
- stainless steel (INOX) clamp profile
- double-layer

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	
1,5 / 38	1.969	11.386	13.289	0.827	0.383	25	450-0038-0000
- / 40	2.047	11.096	12.993	0.866	0.397	-	450-0040-0000
2 / 50-51	2.441	9.138	11.221	0.984	0.511	25	450-0050-0000
- / 55	2.638	8.702	10.336	1.063	0.551	25	450-0055-0000
2,36 / 60	2.835	8.267	9.450	1.102	0.598	-	450-0060-0000
2,5 / 63-65	3.031	7.905	8.564	1.181	0.645	25	450-0065-0000
- / 70	3.228	7.615	7.678	1.220	0.692	25	450-0070-0000
3 / 75-76	3.425	7.252	6.792	1.299	0.739	25	450-0075-0000
- / 80	3.622	7.034	5.906	1.339	0.780	-	450-0080-0000
3,5 / 89-90	4.016	6.527	4.134	1.457	0.874	25	450-0090-0000
4 / 100-102	4.409	4.351	3.544	1.102	0.692	25	450-0100-0000
- / 110	4.803	4.134	3.101	1.181	0.759	-	450-0110-0000
4,5 / 114-115	5.000	3.989	2.894	1.260	0.786	12.5 25	450-0115-0000
4,72 / 120	5.197	3.916	2.658	1.260	0.820	-	450-0120-0000
5 / 125-127	5.394	3.771	2.510	1.339	0.853	12.5 25	450-0125-0000
- / 130	5.591	3.699	2.215	1.339	0.887	12.5 25	450-0130-0000
5,5 / 140	5.984	3.553	1.772	1.417	0.954	12.5 25	450-0140-0000
6 / 150-152	6.378	2.393	1.477	1.496	0.699	12.5 25	450-0150-0000
6,3 / 160	6.772	2.321	1.329	1.575	0.746	-	450-0160-0000
6,5 / 165	6.969	2.248	1.181	1.614	0.766	12.5 25	450-0165-0000
- / 170	7.165	2.248	1.181	1.654	0.786	-	450-0170-0000
- / 175	7.362	2.176	1.181	1.732	0.813	12.5 25	450-0175-0000
7 / 178-180	7.559	2.176	1.181	1.732	0.833	12.5 25	450-0180-0000
8 / 200-203	8.346	2.031	0.886	1.890	0.921	12.5 25	450-0200-0000
- / 215	8.937	1.958	0.886	2.047	0.988	12.5 25	450-0215-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

CP HYP 450

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	
- / 225	9.331	1.886	0.738	2.126	1.035	-	450-0225-0000
9 / 228-229	9.449	1.886	0.738	2.244	1.048	12.5 25	450-0228-0000
- / 250	10.315	1.450	0.738	2.283	1.149	-	450-0250-0000
10 / 254	10.472	1.378	0.738	2.362	1.243	12.5 25	450-0254-0000
- / 275	11.299	1.305	0.591	2.520	1.257	12.5 25	450-0275-0000
11 / 280	11.496	1.305	0.591	2.559	1.317	12.5 25	450-0280-0000
- / 300	12.283	1.233	0.443	2.677	1.371	-	450-0300-0000
12 / 305	12.480	1.233	0.443	2.717	1.391	12.5 25	450-0305-0000
- / 315	12.874	1.233	0.443	2.795	1.438	12.5 25	450-0315-0000
- / 325	13.268	1.160	0.443	2.913	1.485	12.5 25	450-0325-0000
13 / 330	13.465	1.160	0.443	2.953	1.512	12.5 25	450-0330-0000
- / 350	14.252	0.943	0.443	3.071	1.593	-	450-0350-0000
- / 400	16.220	0.870	0.295	3.465	1.821	-	450-0400-0000
16 / 405-406	16.457	0.798	0.295	3.543	1.848	12.5 25	450-0406-0000
- / 450	18.189	0.798	0.295	3.858	2.043	-	450-0450-0000
18 / 457	18.465	0.725	0.295	3.937	2.077	12.5 25	450-0457-0000
- / 500	20.157	0.725	0.148	4.252	2.265	-	450-0500-0000
20 / 508	20.472	0.508	0.148	4.331	2.292	12.5 25	450-0508-0000
- / 600	24.094	0.435	0.148	5.039	2.715	-	450-0600-0000
24 / 610	24.488	0.435	0.148	5.118	2.769	-	450-0610-0000
- / 700	28.031	0.363	0.059	5.827	3.165	-	450-0700-0000
- / 900	35.906	0.290	0.030	7.402	4.059	-	450-0900-0000
- / 1000	39.843	0.290	0.030	8.189	4.509	-	450-1000-0000

Accessories



CONNECT 228



CONNECT 270-271



CLAMP 213



CLAMP 212



CLAMP 217

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.