



NORPLAST® PUR 386 SCIROPPO® PU FOOD AS



Food quality, abrasion resistant suction and discharge hose

Applications

- for powdery or granular food up to 104°F

Properties

- increased pressure and vacuum resistance
- very flexible and wear resistant
- according to the norm EN ISO 1307:2008

Temperature range

- 5°F to 140°F

Design

- polyurethane inner layer
- PVC outer layer
- corrugated construction cover

- rigid PVC spiral
- With copper stranded wire
- PU wall 0,02 inch
- smooth interior

Delivery variants

- transparent inner tube, transparent exterior wall, orange spiral (standard)

I.D.	outer Ø	Vacuum	Operating pressure (68°F)	Bending radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(in)	(inHG)	(bar)	(in)	(lb/ft)	(ft)	
1,5 / 38	1.811	20.671	7,000	6.299	0.410	60	4603-038-000
- / 40	1.890	20.671	7,000	6.693	0.437	30	4603-040-000
2 / 51	2.402	20.671	6,500	8.268	0.618	60	4603-050-000
2,36 / 60	2.756	20.671	5,000	9.449	0.773	30	4603-060-000
3 / 76	3.465	20.671	4,000	12.205	1.042	60	4603-075-000
4 / 102	4.528	20.671	3,500	16.142	1.647	60	4603-100-000

Accessories



CLAMP 211