PRO$_2$AIR Pre-PUR 601



Membrane tube diffuser

Applications
- membrane tube diffusor, for industrial and municipal wastewater treatment plant, pressure diffusion with fine bubbles, oxygen input for nitrication in activation basins, permanent and intermittend ventilation
- oxygen input and circulation in xed-bed and bioreactors, thorough mixing of activation basins, sand trap louvre ventilation, renaturation of lakes and rivers, aquacultures, sh farming

Properties
- high energy savings when compared with comparative, market standard EPDM and silicone diffusors due to the much lower pressure loss
- extremely long lifetime and no curing due to the membrane not including a plasticizer
- very wide operating range: normal operation: 3-8, minimum 1, maximum 15 and purging operation 18 Nm^3/(h*m_{aer.})
- comparatively high oxygen input and oxygen transfer efficiency even with low density systems
- very fine and uniform bubble formation due to an optimized perforation
- easily and quickly fitted
- extremely tear-resistant and abrasion-resistant (mechanical strength around 2.5-4 times that of most of the EPDM and silicone materials)
- very good resistance to waste water and municipal sewerage in accordance with the latest instructions DWA-M 115
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline

Temperature Range
- -40 °C to 90 °C

Design
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 0,6 mm approx.
- Support body: polypropylene
- clamps: stainless steel 1.4301/AISI 304/W2/INOX

Delivery variants
- further diameters and lengths available on request
- transparent (standard)
- special colours: full coloured
- customer-specific branding


Size (mm)	I.D. (in / mm)	Inner Thread (inch)	Length (mm)	Ventilation Length (mm)	Weight (kg/pcs)	Order No.
Dimension in Stock; Clamps: stainless steel (INOX) 1.4301 (stamped) = AISI 304						
63	64,5	3/4	570	500	0,700	601-0570-2702
63	64,5	3/4	820	750	1,000	601-0820-2702
63	64,5	3/4	1070	1000	1,300	601-1070-2702
Further production lengths; Clamps: stainless steel (INOX) 1.4301 (stamped) = AISI 304						
63	64,5	1	570	500	0,700	601-0570-2712
63	64,5	1	820	750	1,000	601-0820-2712
63	64,5	1	1070	1000	1,300	601-1070-2712
Further production lengths; Clamps: stainless steel (INOX) 1.4571 (stamped) = AISI 316Ti						
63	64,5	3/4	570	500	0,700	601-0570-2722
63	64,5	1	570	500	0,700	601-0570-2742
63	64,5	3/4	820	750	1,000	601-0820-2722

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.


PRO$_2$AIR Pre-PUR 601

Size (mm)	I.D. (in / mm)	Inner Thread (inch)	Length (mm)	Ventilation Length (mm)	Weight (kg/pcs)	Order No.
63	64,5	1	820	750	1,000	601-0820-2742
63	64,5	3/4	1070	1000	1,300	601-1070-2722
63	64,5	1	1070	1000	1,300	601-1070-2742

Accessories



CONNECT 683



CONNECT 685



CONNECT 684

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.