



Membrane tube diffuser longer lengths for mounting without support body

Applications

- membrane tube diffusor, for industrial and municipal wastewater treatment plant, pressure diffusion with fine bubbles, oxygen input for nitrification in activation basins, permanent and intermittent ventilation
- oxygen input and circulation in xed-bed and bioreactors, thorough mixing of activation basins, sand trap louvre ventilation, renaturation of lakes and rivers, aquacultures, sh farming

Properties

- high energy savings when compared with comparative, market standard EPDM and silicone diffusers due to the much lower pressure loss
- extremely long lifetime and no curing due to the membrane not including a plasticizer
- very wide operating range: normal operation: 3-8, minimum 1, maximum 15 and purging operation 18 Nm³/(h*m_{aer.})
- comparatively high oxygen input and oxygen transfer efficiency even with low density systems

- very fine and uniform bubble formation due to an optimized perforation
- easily and quickly fitted
- very good resistance to waste water and municipal sewerage in accordance with the latest instructions DWA-M 115
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline

Temperature Range

- -40 °C to 90 °C

Design

- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 0,7 mm approx.

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colours: full coloured
- customer-specific branding

Size	I.D.	Length	Weight	Order No.
(mm)	(mm)	(m)	(kg/pcs)	
63	64,5	2	0,360	622-0020-2702
63	64,5	5	0,900	622-0050-2702
63	64,5	10	1,800	622-0100-2702
63	64,5	20	3,600	622-0200-2702
63	64,5	25	4,500	622-0250-2702
63	64,5	30	5,400	622-0300-2702
63	64,5	40	7,100	622-0400-2702
63	64,5	50	9,000	622-0500-2702

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.