



Adapter body for assembly of membrane diffuser tubes

Applications

- membrane tube diffusor, for industrial and municipal wastewater treatment plant, pressure diffusion with fine bubbles, oxygen input for nitration in activation basins, permanent and intermittend ventilation

- oxygen input and circulation in xed-bed and bioreactors, thorough mixing of activation basins, sand trap louvre ventilation, renaturation of lakes and rivers, aquacultures, sh farming

Properties

- conforms to RoHS guideline

Design

- Support body: polypropylene

Size (in)	Inner thread (inch)	Length (in)	hose length (in)	Weight (lb/pcs)	Order No.
2.480	3/4	22.441	22.441	1.103	681-0570-2700
2.480	1	22.441	22.441	1.103	681-0570-2743
2.480	3/4	32.283	32.283	1.654	681-0820-2700
2.480	1	32.283	32.283	1.654	681-0820-2743
2.480	3/4	42.126	42.126	1.676	681-1070-2700
2.480	1	42.126	42.126	1.676	681-1070-2743

Accessories



CONNECT 685



CLAMP 682



CONNECT 683



CONNECT 684

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.