



Connector for mounting membrane tube diffusers on rectangular profiles from both sides

## Applications

- membrane tube diffusor, for industrial and municipal wastewater treatment plant, pressure diffusion with fine bubbles, oxygen input for nitration in activation basins, permanent and intermittend ventilation

- oxygen input and circulation in xed-bed and bioreactors, thorough mixing of activation basins, sand trap louvre ventilation, renaturation of lakes and rivers, aquacultures, sh farming

## Properties

- conforms to RoHS guideline

## Design

- Stainless Steel (INOX) 1.4541 = AISI 321

Length (mm)	profile width (mm)	Outer thread (in)	Weight (kg/pcs)	Order No.
85	40	3/4"	0,110	684-0085-2770
105	60	3/4"	0,140	684-0105-2770
125	80	3/4"	0,170	684-0125-2770
145	100	3/4"	0,190	684-0145-2770

## Accessories



CONNECT 681



CONNECT 685



CLAMP 682



CONNECT 683

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).